




Order example:

1 x LLB550-50klb

Quantity Part No.


Email to sales@loadcellsensor.com for a quote

Specifications			
Rated Capacity	10/20/30/50klb		
Rated Output	2.0 mV/V	Compensated Temp.	0...+60°C
Excitation	3~15V	Operating Temp.	-20...+80°C
Zero Balance	±0.05 mV/V	Temp. Coeff. of Zero	±0.01% F.S./°C
Nonlinearity	±0.3% F.S.	Temp. Coeff. of Span	±0.02% F.S./°C
Hysteresis	±0.3% F.S.	Input Resistance	750±50 Ohms
Nonrepeatability	±0.1% F.S.	Output Resistance	700±10 Ohms
Creep(30min)	±0.1% F.S.	Insulation Resistance	>2000M Ohms(50V)
Safe Load Limit	150% F.S.	IP Rating	IP67
Breaking Load	200% F.S.	Element Material	Stainless steel
Cable	Ø5.2*2000mm 4-conductor shielded cable		


• LCS reserves the right to modify its design and specifications without notice

P:1/2

Load direction



Wiring Code



Shield is connected to the sensor body

Sensor/Amplifier/Indicator

Items	Power supply	Output/Function
LLB550	3-15V (Constant)	0mV...+30mV (Depending on the power supply)
LLB550 + Analog amplifier	12~24V DC	0-3.3V,0-5V,0-10V, 0-20mA,4-20mA...
LLB550 + Digital amplifier	12~24V DC	RS485 or RS232 output
LLB550 + Indicator	12~24V DC	Display force value Switch/Relay output Peak holding RS485/RS232 interface 0-5V/0-10V/4-20mA output
Email us for datasheet of amplifier and indicator		

Customization options

Cable (Length/Specifications/Connectors)
Dimensions and measuring range
Working Temperature (-40°C...+200°C)